



					
4.3	7	7	10.1	10.1	15.6
85/85/85/85	60/70/70/70	60/70/70/70	60/70/70/70	60/70/70/70	85/85/85/85
480*272	800*480	800*480	1024*600	1024*600	1920*1080
350	400	400	400	400	300
400:1	400:1	400:1	400:1	400:1	400:1
30000	50000	50000	50000	50000	50000
16.7M	16.7M	16.7M	16.7M	16.7M	16.7M
4					
ARM Co r ex-A7 1.2Ghz					ARM Co r ex-A53 1.5Ghz
128M+128M					8G+1G
10M/100M *1					
USB 2.0*1					
COM1:RS485 COM2:RS422/485 COM3:RS232	COM1:RS485	COM1:RS485 COM2:RS422/485 COM3:RS232	COM1:RS485	COM1:RS485 COM2:RS422/485 COM3:RS232	COM1:RS485 COM2:RS422/485 COM3:RS232
2.4W	4.8W	4.8W	7.2W	7.2W	14.4W
DC24V (-15% 20%)					
5ms					
EN61000-6-2:2005 EN61000-6-4:2007					
RoHS		±500V 4KV	±2KV 8KV		
IP65		IP20	GB/T 4208		
5		150Hz(X/Y/Z	1g/3.5mm)		
0 55					
-25 70 ()					
10% 95%()					
CE					
					PET
					VESA
119.00*93.00	193.00*139.00	193.00*139.00	259.00*201.00	259.00*201.00	384.00*247.00
128.00*102.00*35.20	210.00*156.00*42.20	210.00*156.00*42.20	276.00*218.00*43.20	276.00*218.00*43.20	398.10*260.10*35.90
285	642	642	1095	1095	2650
HC Touch VPro					
/U					

||



